

PRODUCT HAZARDS

AMENDED 30th JUNE 2006

ALBION ARCHITECTURAL CONCRETE

Unit C7 Newbrook Works

Pound Lane

Upper Beeding

West Sussex

BN44 3JD

Tel: 01903-815262

Fax: 01903-815619

Albionart.co.uk

This data sheet is a formal notification as required by Section 6 of the Health & Safety at Work Act, as amended by the Consumer Protection Act 1987. This legislation requires us to provide customers with certain information pertaining to the properties and safe use of our products. It is important that this information is distributed to all relevant personnel and/or sub-contractors or other parties employed by yourselves in the handling and use of these materials.

PRODUCTS

Precast concrete products manufactured and marketed by ALBION ARCHITECTURAL CONCRETE comprise of Pavers, Blocks, Architectural Cast Stone Units and Bespoke Precast items. They are produced from the normal constituents of concrete, and when presented in their normal form and manner are unlikely to give rise to any significant risk to health.

The normal constituents are:

- Natural and Artificial Aggregates
- Cementing Agents
- Additional Binders
- Non-Toxic Iron Oxide Pigments
- Steel Reinforcement
- Steel Fixings

PHYSICAL AND CHEMICAL CHARACTERISTICS

Precast concrete products are manufactured to fine tolerances by the compaction and/or vibration of a hydrated mix of constituent materials which subsequently undergo a curing process. Precast concrete of this nature can be considered to be inert and therefore presents no major chemical hazard.

MAIN HAZARDS

Handling of precast concrete products may cause abrasive damage to the hands. Excessive handling may cause dermatitis or drying of unprotected skin. Manual handling of precast concrete should only take place where the weight of the unit(s) permits, otherwise injury may occur. Weights of products are available from the supplying works. Cutting, drilling, grinding or

similar treatment of the products will give rise to respirable dust. Such dust, if inhaled in excessive quantities over extended periods, can constitute a long-term health hazard. Cutting, unless adequately controlled, can project particles at high velocity, with consequent risk of impact damage. Wet cutting is recommended. Steel reinforcement, which may be integrated into some precast units, may constitute a fire hazard from the resultant sparks if the units are to be cut.

CLEANING AND MAINTENANCE

Periodic cleaning may be carried out by washing with water and mild detergents using soft brushes. For more aggressive cleaning refer to specialist concrete cleaning agencies.

Aggressive cleaning with high-pressure washers and/or diluted acids will leave units with a coarser texture which will change the apparent colour.

PRECAUTIONS

During cutting or similar surface treatment, inhalation of dust should be avoided and eyes protected. When working with heavy, dense, cementitious building products, personal protective clothing such as gloves and protective footwear should be worn. Care should be taken when handling heavy components, and mechanical lifting equipment should be used in accordance with the Manual Handling Regulations. Care is required when cutting and disposing of any plastic/nylon bands to avoid injury. Gloves and goggles should be worn.

TRANSPORTATION AND STORAGE

The carriage of precast concrete products is not subject to hazardous substance conveyance regulations and vehicle labelling is not required. Particular care should be taken in the handling and stacking of units or packs of units, taking into account the weight, method of handling, condition of the ground, and stability of the packs.

WASTE DISPOSAL

Hardened concrete is inert but should be disposed of in accordance with local regulations. In some cases reinforced concrete will need to be separated from unreinforced concrete prior to disposal. Products may be delivered in packaging that comprises polythene covers, plastic/nylon strapping and wooden pallets. All types of packaging require careful site disposal after use. In particular the haphazard burning of polythene covers and of wooden pallets will, in themselves, release smoke and fumes which can be inhaled in sufficient quantities to be injurious to health.